

1425 Highway 25 N.
Tishomingo, MS 38873




800-255-4345
www.duraclass.com

DuraClass® Hy-Flo™ Twin Electric Power Unit

Unit features include fast cycle time & simplified operation for multiple users


DuraClass® is pleased to announce that we are now offering the DuraClass Hy-Flo™ Twin Electric Power Unit. This unit is available for use with select DuraClass hoists.

This system offers **3x** the capacity of the standard electric double-acting unit, and also offers up to **1.2x** the capacity of a PTO at idle.



Ordered in lieu of direct mount hydraulics, the DuraClass Hy-Flo Twin Electric Power Unit offers features and benefits that meet and exceed current systems:

- Can save you up to **\$1,500**, and cut installation time by up to 2/3
- Save up to **\$500** off of the cost of your chassis when ordering – no PTO option required
- Push button control for simple operation
- No chance of leaving PTO engaged
- Can help your customer with Idle Restrictions
- No linkages



Specifications of this unit include:

- Number of Motors / Pumps	2
- Voltage	12 VDC
- Avg Current Draw per Motor (loaded body)	231 Amps
- Nominal Flow	6 GPM
- Average Flow (loaded body)	3.3 GPM
- Rated Pressure	3200 PSI
- Batteries Required	2

The DuraClass Hy-Flo Twin Electric Power Unit can be used with the following hoists:

- 1520
- LR26
- LR623
- LR28
- E15

For more information on the DuraClass Hy-Flo Twin Electric Power Unit, please contact your Territory Manager or DuraClass Inside Sales.